## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 20 January 2005 (20.01.2005)

PCT

(10) International Publication Number WO 2005/006777 A3

(51) International Patent Classification7:

H04N 13/00

(21) International Application Number:

PCT/GB2004/002975

(22) International Filing Date:

9 July 2004 (09.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0316221.1


10 July 2003 (10.07.2003)

- (71) Applicant (for all designated States except US): OCUITY LIMITED [GB/GB]; 77 Heyford Park, Upper Heyford, Oxfordshire OX25 5HD (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HARROLD. Jonathan [GB/GB]; 8 Robins Grove, Warwick, Warwickshire CV34 6RF (GB). WOODGATE, Graham, John [GB/GB]; 9 Vicarage Road, Henley-on-Thames, Oxfordshire RG9 1HF (GB).

- (74) Agents: MERRYWEATHER, Colin, Henry et al.; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5JJ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM. TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PIXEL ARRANGEMENT FOR AN AUTOSTEREOSCOPIC DISPLAY APPARATUS



(57) Abstract: An autostereoscopic display apparatus comprises a spatial light modulator comprising an array of pixels arranged in rows and columns in a pixel plane, and a spatially multiplexing parallax element capable of directing light from successive columns of pixels towards successive ones of two or more viewing windows in a nominal window plane. The pixels comprise pixel apertures having gaps therebetween with the gaps between the columns of pixels extending substantially parallel to the columns of pixels. The arrangement of the pixels is designed taking account of the intensity profile of an image of a nominal human pupil in the nominal window plane formed in the pixel plane by the spatially multiplexing parallax element to reduce the amount of spatially derived flicker observed by a viewer moving in the window plane. In one arrangement, the pixel apertures repeat at a pitch equal to a representative width of said intensity profile. In another arrangement, the total height of the pixel apertures parallel to the columns of pixels has a profile which increases towards the edges of the pixel apertures relative to the centre of the pixel apertures.







## **Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
17 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.